

PO Box 5, Morley, LS27 0QP Page Nepshaw Lane South, Morley, Leeds Tel 0113 253 0241 Fax 0113 252 7029 Head of Laboratory G. Briggs C. Text ATI

Client:	Camira Fabrics Ltd Meltham Mills Meltham West Yorkshire HD9 4AY
Entry No:	58239
Date received:	23/08/2012
Client's Description:	Sample of fabric: Xtreme Plus
	TEST REPORT
Test Required:	Flammability BS 7176 Medium Hazard
Pre-treatment:	None
Conditioning:	A minimum of 24 hours at 50 +/- 5% Relative Humidity, 23 +/- 2°C
Method of Test:	BS EN 1021-1: 2006 – smouldering cigarette BS EN 1021-2: 2006 – match flame equivalent
Date of Test:	29/08/2012

Ignition Source	Observations	Result
Smouldering	No flaming or progressive smouldering was observed within one	PASS
cigarette	hour of placement of the cigarettes.	
Match flame equivalent	Flaming ceased within the specified two minute period after removal of the butane flame and no progressive smouldering occurred.	PASS

Note: A 35 kg/m³ CMHR Foam (Carpenters RX36-125) which meets the requirements of Annex A of BS 7176+ A1:2011 was used as the filling

The above tests relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

-----End of Page-----

This is hereby certified to be a correct return of the tests made of the items referred to herein.

D J Brockbank Senior Technologist 30 August 2012



Unless instructed otherwise by the client sample remnants will be disposed of after 28 days Test marked (*) in this certificate are not included in the UKAS Accreditation Schedule for this Laboratory.

Opinions and interpretations expressed herein are outside the scope of UKAS accreditation.
This Certificate relates only to the sample received and, unless that sample has been drawn by the staff of this laboratory, or its agent, and endorsed accordingly, any application of the result to a bulk quantity or other material is entirely the responsibility of the client.





PO Box 5, Morley, LS27 0QP Page Nepshaw Lane South, Morley, Leeds Tel 0113 253 0241 Fax 0113 252 7029 Head of Laboratory G. Briggs C. Text ATI

Client:	Camira Fabrics Ltd Meltham Mills Meltham West Yorkshire HD9 4AY
Entry No:	58239
Method of Test:	BS 5852 : 2006 Clause 11 (composites)
Pre-treatment:	None
Conditioning:	A minimum of 96 hours at 50 +/- 5% Relative Humidity, 23 +/- 2°C
Date of Test:	29/08/2012

The following test results relate only to the ignitability of the combination of upholstery composites under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.

Ignition Source	Observations	Result
5 (Wood Crib)	Flaming ceased within the specified ten minute period after	PASS
	ignition of the crib and no progressive smouldering occurred.	

Note: A 35 kg/m³ CMHR Foam (Carpenters RX36-125) which meets the requirements of Annex A of BS 7176 + A1:2011 was used as the filling

Comments

BS 7176 : 2007 + A1 : 2011 relates to labelling of furniture. If an item of furniture was manufactured from a composite of the fabric and foam tested above then it would comply with the medium hazard category requirements provided that it was tested every 2.500 units or once per month as required by Para 5 of BS 7176.

-----End of Document------

This is hereby certified to be a correct return of the tests made of the items referred to herein.



D J Brockbank Senior Technologist 30 August 2012



Unless instructed otherwise by the client sample remnants will be disposed of after 28 days Test marked (*) in this certificate are not included in the UKAS Accreditation Schedule for this Laboratory.

Opinions and interpretations expressed herein are outside the scope of UKAS accreditation.
This Certificate relates only to the sample received and, unless that sample has been drawn by the staff of this laboratory, or its agent, and endorsed accordingly, any application of the result to a bulk quantity or other material is entirely the responsibility of the client.

